Network Programming with Python

Cheat Sheet Series — comparitech

Required common installation modules: PIP and IDLE

PIP (Python Package Installer)	`$ sudo apt-get install python-pip`
IDLE (Integrated Development and Learning Environment)	`$ sudo apt-get install idle`

Top Python Network Programming Libraries

Django	High-level Python Web framework for rapid development and pragmatic
pycos (formerly asyncoro)	Python framework for asynchronous, concurrent, network, distributed programming and distributed computing
Diesel	A clean API for writing network clients and servers. TCP and UDP supported. Bundles clients for HTTP, DNS, Redis, Riak and MongoDB.
Pulsar	Easy way to build scalable network programs
Twisted	Event-based framework for internet applications: HTTP clients and servers, SSHv2 and Telnet, IRC, XMPP, IMAPv4, POP3, SMTP, IMAPv4, POP3, SMTP, etc.
NAPALM	Network Automation and Programmability Abstraction Layer with Multivendor support - For dealing with dvice vendors
gevent	A coroutine -based Python networking library that uses greenlet to provide a high-level synchronous API on top of the libev or libuv event loop
Celery	Asynchronous task queue/job queue based on distributed message passing

Data Types

Text	str - *x = "Hello World"*
Numeric	int, float, complex
Sequence	list, tuple, range
Mapping	dict
Set	set, frozenset
Boolean	bool
Binary	bytes, bytearray, memoryview

Math Operators

**	Exponent ***4 ** 2 = 16***
%	Modulus/Remainder ***43 % 5 = 3***
//	Integer division ***11 // 5 = 2***
/	Division ***11 / 5 = 2.2***
*	Multiplication ***3 * 3 = 9***
-	Subtraction ***8 - 3 = 5***
+	Addition ***2 + 2 = 4***
==	Equal to
!=	Not equal to
<	Less than
>	Greater Than
<=	Less than or Equal to
>=	Greater than or Equal to
#	Can be used at the beginning of a line, or from within a line to the end of the line

Socket Module (Berkley API interface)

Primary Functions an Methods	socket() • ind() • listen() • accept() • connect() • connect_ex() • send() • recv() • close()

Server-side socket example

```
import socket
s=socket.socket(socket.AF_INET,socket.SOCK_STREAM)
host=socket.gethostname()
port=1111
myserver.bind((host,port)) # replace myserver and myclient with
respective IPs
myserver.listen(5)
while True:
myclient,addr=myserver.accept()
print("Connected to {str(addr)}")
myclient.send(msg.encode("ascii"))
myclient.close()
```

Network forensics: Required python libraries and scripts

EDDIE Tool	System and network monitoring, security, and performance analysis agent for python
pypcap	Small packet capture tool based on python and pcap
Paramiko	Implementation of the SSHv2 protocol, providing both client and server functionality
pip	Package installer for python
The Python Package Index (PyPI)	Repository of software for the Python

Python Keywords

del	Delete objects
else	Conditional statement
except	Used in try-except blocks in error handling
finally	Used in try-except blocks in error handling, runs with or without errors
in	Check a value include in a sequence
import	Import module to current environment
lambda	Anonymous function
print	Standard print
try	Used in error handling

dnspython library

Installation

```
$ pip install dnspython
```

Basic DNS query

```
import dns.resolver
name = 'google.com'
for qtype in 'A', 'AAAA', 'MX', 'NS', 'TXT', 'SOA':
answer = dns.resolver.query(name,qtype, raise_on_no_answer=False)
if answer.rrset is not None:
print(answer.rrset)
```

Get MX target and name preference

```
import dns.resolver

answers = dns.resolver.query('dnspython.org', 'MX')
for rdata in answers:
print ('Host', rdata.exchange, 'has preference', rdata.preference)
```

Server-side socket example

```
import socket

HOST = '' # Symbolic name meaning all available interfaces
PORT = 52542 # Arbitrary non-privileged port
s = socket.socket(socket.AF_INET, socket.SOCK_STREAM)
s.bind((HOST, PORT))
s.listen(1)
conn, addr = s.accept()
print ('Connected by', addr)
while 1:
data = conn.recv(1024)
if not data: break
conn.sendall(data)
conn.close()
```

Socket Errors / Exceptions

exception socket.error	A deprecated alias of OSError, raised when a system function returns a system-related error
exception socket.herror	raised for address-related errors by getaddrinfo() and getnameinfo()
exception socket.gaierror	raised when a timeout occurs on a socket which has had timeouts enabled via a prior call to settimeout() (or implicitly through setdefaulttimeout()
exception socket.timeout	

Server-side socket example with Comments

```
# Echo server program
# Import socket module
import socket

# Create a socket object
s = socket.socket()

# Define the port on which you want to
connect
port=1111

# connect to the server on local
computer
s.connect(('172.18.0.1', port))

# receive data from the server
print (s.recv(1024))
# close the connection
s.close()
```

Network Analysis with Python

Use NMAP with port scanner	`$ pip install python-nmap`

Commands to run NMAP scan

```
import nmap
nmScan = nmap.PortScanner()
nmScan.scan('10.1.0.0', '25-443')
```

NMAP commands used with python

```
nmScan.scaninfo() # {'tcp': {'services': '25-80', 'method': 'connect'}}

nmScan.all_hosts()

nmScan['10.1.0.0'].hostname()

nmScan['10.1.0.0'].state()

nmScan['10.1.0.0'].all_protocols()

nmScan['10.1.0.0']['tcp'].keys() # Results -[80, 25, 22, 135]

nmScan['10.1.0.0'].has_tcp(25) # Result –True/False

nmScan['10.1.0.0'].has_tcp(21) # Result False/True
```

Parsing Modules

argparse()	The argparse module makes it easy to write user-friendly command-line interfaces. The program defines what arguments it requires, and argparse will figure out how to parse those out of sys.argv
Creating a parser	`>>> parser = argparse.ArgumentParser(description='Process some integers.')`

Adding arguments	`>>> parser.add_argument('integers', metavar='N', type=int, nargs='+',`
	`... help='an integer for the accumulator')`
	`>>> parser.add_argument('--sum', dest='accumulate', action='store_const',`
	`... const=sum, default=max,`
	`... help='sum the integers (default: find the max)')`

Parsing arguments	`>>> parser.parse_args(['--sum', '7', '-1', '42'])` `Namespace(accumulate=<built-in function sum>, integers=[7, -1, 42])`

Socket Types

SOCK_STREAM	For TCP protocols • Reliable transmission • Packet sequence • Connection-oriented • Bidirectional
SOCK_DGRAM	For UDP protocols • Unreliable transmission • No sequence of packets • Connectionless(UDP) • Not Bidirectional

Create a socket

```
import socket # Imports the socket method

socket.socket() # Function that creates socket
```

sock = socket. socket (*socket family*, *socket type*, *protocol=value*)

Socket Family	**AF_UNIX** or **AF_INET**
Socket Type	**SOCK_STREAM** or **SOCK_DGRAM** for TCP & UDP respectively • e.g. TCP - UDP2 = socket. socket (socket.AF_INET, socket.SOCK_DGRAM) • e.g. UDP - TCP2 = socket. socket (socket.AF_INET, socket.SOCK_STREAM)
Client socket method	`connect()`
Server socket method	`bind() • listen(backlog) • accept()`
TCP socket methods	`s.recv() # Receive TCP packets` `s.send() #Send TCP packets`
UDP socket methods	`s.recvfrom() # Receives UDP packets` `s.sendto() # Transmits UDP packets`

More Socket Methods

close()	Close the socket connection
gethostname()	Returns a string which includes the hostname of the current PC
gethostbyname()	Returns a string which includes the hostname and IP address of the current PC
listen()	Setup and start TCP listener
bind()	Attach (host-name, port number) to the socket
accept()	TCP client connection wait
connect()	Initiate TCP server connection

TCP Socket Methods

mysocket.accept()	Returns a tuple with the remote address that has connected
mysocket.bind(address)	Attach the specified local address to the socket
mysocket.connect(address)	Data sent through the socket assigns to the given remote address
mysocket.getpeername()	Returns the remote address where the socket is connected
mysocket.getsockname()	Returns the address of the socket's own local endpoint
mysocket.sendto(data, address)	Force a data packet to a specific remote address

Socket Blocking

setblocking(1)	Setup block
setblocking(0)	Remove / un-setup block

Get port number using domain name

```
import socket

socket.getservbyname('domain name')
```

Check support for IPV6

```
import socket
socket.has_ipv6 # Answer is TRUE or FALSE
```

getaddrinfo() - Bind Server to a Port

```
from socket import getaddrinfo
getaddrinfo(None, 'FTP', 0, socket.SOCK_STREAM, 0, socket.AI_PASSIVE)
[(2, 1, 6, '', ('0.0.0.0', 21)), (10, 1, 6, '', ('::', 21, 0, 0))]
```

Script Examples

Create list of devices

```
>>>devices = ['SW1', 'SW2', 'SW3']
```

Create VLAN dictionary list

```
vlans = [{'id': '100', 'name': 'staff'}, {'id': '200', 'name':
'VOICE'},
{'id': '300', 'name': 'wireless'}]
```

Write functions to collect commands and push to the network

```
>>>def get_commands(vlan, name):
      commands = []
      commands.append('vlan ' + vlan)
       commands.append('name ' + name)

       return commands

>>> def push_commands(device, commands):
      print('Connecting to device: ' + device)
       for cmd in commands:
       print('Sending command: ' + cmd)
```

Create VLANs in multiple switches using python script

```
>>>for vlan in vlans:
id = vlan.get('id')
name = vlan.get('name')
print('\n')
print('Configure VLAN:' + id)
commands = get_commands(id, name)
for device in devices:
           push_commands(device, commands)
           print('\n')
```

Citation: https://www.oreilly.com/library/view/network-programmability-and/9781491931240/ch04.html

Disable router interface using python command

```
>>> from push import push_commands
device = 'router2'
commands = ['interface Eth0/1', 'shutdown']
      push_commands(device, commands)
```